

TotalBoat White Knight - Stain Remover -- Tech Data Sheet

SUPPORT PRODUCTS:

Products Commonly used with White Knight: TotalBoat TotalBuff, TotalBoat TotalShine, TotalBoat Boat Soap, TotalBoat Fiberglass Polish, TotalBoat Premium Boat Wax

APPLICATION:

SUBSTRATES:	For use on fiberglass, gelcoat, and painted surfaces. Test any painted surfaces in a small, inconspicuous spot before full application.
GENERAL APPLICATION:	
1	Use rubber gloves when applying. Wet the area before application.
2	Always test in a small, inconspicuous spot before attempting a large area.
3	Using a brush or rag, apply a thin layer of TotalBoat White Knight to the surface and allow 10-15 minutes for it to work, then scrub with a soft brush or sponge.
4	Thoroughly rinse the surface with water to remove White Knight before it dries.
5	Some tough stains may need a second application. Always protect the surface after application with TotalBoat Premium Boat Wax or Polish.
Note:	Always wipe away thoroughly before White Knight dries out as it will require more effort to remove when it has dried. Always use proper safety equipment when applying and removing White Knight.

APPLICATION DATA:

Application Method:	Rag, terrycloth towel, chip brush
Substrates:	For use on fiberglass, gelcoat, and painted surfaces (always test any painted surfaces in a small, inconspicuous spot before full application)
Number of Applications:	One application will remove most stains; tough stains may require a second
Cleanup:	Water
Coverage (sq ft/gal):	N/A
Application Temp/RH:	40-100°F, 0-90%

PHYSICAL DATA:

Color:	Light blue - washes away when the product is completely removed
Components:	One
Finish:	N/A
Storage:	Cool, dry area
Flash Point:	N/A
Units:	15 oz.
Solids (% by Volume):	N/A
VOC (lb/gal):	N/A